

310 E. LANARK AVENUE, LANARK, ILLINOIS 61046 PHONE: 815-493-6360 FAX: 815-493-2371 www.forsterproducts.com

User Instructions for the Power Case Trimmer

1.0 GENERAL INFORMATION

- Fits on most standard drill presses (see Fig. 1).
- Specifications are the same as our Original Case Trimmer.
- The staggered tooth, high alloy steel cutter shaft provides fast, smooth, chatterless cutting.
- Superior shell holder design is based on a Brown & Sharpetype collet that provides consistent length, case after case.
- Collets and Pilots are interchangeable with the Original Case Trimmer. Use our online database to determine which Pilots and Collets are right for the job. Go to <u>www.forsterproducts.com</u> and click on the Search tab. Pilots and Collets are available separately (see Section 6.0).
- Accommodates all six case trimmer accessories (see Section 8.0).

Figure 1. Power Case Trimmer Assembled and In Use on Your Drill Press



2.0 SAFETY INFORMATION

Always wear safety glasses.

3.0 PREPARATION (See Fig. 2)

• The Collet Screw and Collet Housing come out of the box fully assembled onto the Base (PT1010-013). In order to insert a Collet into the Collet Screw, these components need to be disassembled. Use the provided 5/32 Allen Wrench on the 10-32x3/4 Socket Head Cap Screw to remove the Collet Housing/Collet Screw assembly.

Figure 2. Power Case Trimmer Unassembled



- Have handy the following items:
 - Reliable manual to consult for correct case lengths.
 - Caliper for checking case lengths.
 - Grease.

NOTICE DRILL PRESS PRECISION

Ensure you periodically check and adjust your drill press for excessive vibration, play and wobble (runout), three factors that can negatively affect the performance of your drill press, and ultimately, the precision of the trimmed cases.


Issue 4

4.0 PROCEDURE

4.1 Assemble Collet (See Fig. 3)

- 1. Select the correct Collet for the case to be trimmed (see Section 1.0).
- 2. Apply a very small amount of grease to the front face and tapered portion of the Collet.
- 3. Place the Collet in the Collet Screw, then place the Collet Housing over the Collet Screw.
- 4. Turn the Collet Screw by hand until the Collet just touches the Collet Housing.
- 5. Re-fasten the Collet Screw/Collet Housing assembly to the Base using the 10-32x3/4 Socket Head Cap Screw.
- 6. Screw the Collet Locking Handle into the hole at the bottom of the Collet Screw.

Figure 3. Collet Assembly



4.2 Line Up Power Case Trimmer with Drill Press Spindle (See Fig. 4)

- Place one end of the Line-Up Bar in the Collet and lock it in place by turning the Collet Locking Handle counter clockwise.
- 2. Place the other end of the Line-Up bar in the drill press chuck and lock it in place.

Figure 4. Line-up Bar in Use



4.3 Fasten Power Case Trimmer Base Assembly to Drill Press

- For drill presses with a center hole: Use the 3/8"-16 hole in the center of the Base to attach it to the drill press.
- For drill presses without center holes: Use the outer three holes in the Base and your own mounting screws to securely fasten it to a hardwood board, which may then be held by C-clamps on the drill press table.

4.4 Assemble Pilot in Cutter Shaft

Insert the correct Pilot in the Cutter Shaft. While holding the Pilot firmly against the Cutter Shaft teeth, lock it in place by tightening the Pilot Lock Screw with the provided 5/64" Allen Wrench.

4.5 Insert Case and Adjust for Length

- 1. With tension on the Collet released, insert the base of the case to be trimmed into the Collet.
- 2. Using the drill press quill feed, lower the Pilot into the neck of the case, gently pushing the base of the case against the bottom of the Collet. Ensure the base of the case is held firmly against the bottom of the Collet and the Pilot is supporting the inside case neck, then use the Collet Locking Handle to tighten the Collet Screw.

4.6 Make Trial Cut to Check Case Length NOTICE

CHIP BUILDUP IN THE COLLET

Ensure the collet is cleaned with canned air or a compressor after trimming each case. Chip buildup in the collet will affect the precision of the trimmed cases.

- 1. Set the drill press speed to its lowest setting.
- 2. Lower the drill press quill feed to make a trial cut.
- 3. Remove the case and use a caliper to check its length.
- 4. Use the drill press spindle stop to control desired case length.
- 5. Consult a reliable manual for correct case length.

4.7 Trim Batch of Cases

- 1. The Case Trimmer is now set up to trim a batch of cases to the exact same length.
- 2. Label and save a master setup case that is trimmed to the correct length for each caliber. This will save setup time in future trimming operations.

5.0 AFTER USE

- After trimming, a sharp edge will be evident on the case mouth. The inside and outside of this edge should be chamfered with our Inside-Outside Deburring Tool (DB1000).
- 2. Store the Power Case Trimmer in a cool, dry location.

6.0 ORDERING INFORMATION

6.1 Collets and Pilots

Collet: Determine your case diameter at its rim. See Table 1 and choose the Collet that will accept your case rim.

Pilot: Determine your bullet diameter and order the Pilot which is most appropriate. For example, Pilot #30 (CT1030) will handle all rounds that use a .308" diameter bullet, meaning that one Pilot will work for a variety of calibers, including the 30-06, 308, 30 Carbine, 7.62 NATO and 300 Weatherby Mag. <u>Note: Original and Classic Pilots **are** interchangeable.</u>

Table 1. Power and Original Case Trimmer Collet Step Dimensions

C_/ B_/			B-A			
Collet No.	Α	В	С	Collet No.	Α	В
CT2001 (#1)	.379"	.473"	.532"	CT2004 (#4)	.310"	.605"
CT2002 (#2)	.350"	.418"	.506"			
CT2003 (#3)	.356"	.440"	.545"			

Notes:

- Power and Original Case Trimmers manufactured before June 1, 2010, required a Collet Housing enlargement to .610" when using the #4 Collet; those manufactured after this date already have this modification (see section 7.0).
- #4 Collets manufactured after January 1, 2010, have two steps as shown in Table 1; those manufactured before this date have one step of .605".

6.2 Power Case Trimmer Table 2. Complete Product

Order Number	Description	
PT1010	Power Case Trimmer (includes Base,	
	.490" dia Cutter Shaft and Line-up Bar)	

6.3 Replacement Parts

Every product component is available individually. A complete list of component order numbers and prices is available on our website. Go to **forsterproducts.com**, then click on **Components/Parts List.**

7.0 MACHINING SERVICES

A complete list of services, including prices and lead times, is available on our website. Go to **forsterproducts.com**, then click on **Custom Machining Services.**

7.1 Power and Original Case Trimmer Collet Housing Enlargement (for trimmers manufactured before June 1, 2010)

Use of the #4 Collet requires that the Power and Original Case Trimmer Collet Housing opening be enlarged to .610". This will not affect the use of the #1, #2, or #3 Collet. The Collet Housing can be opened at the factory at no charge. <u>Please return the</u> <u>Collet Housing only. Do not send the entire Case Trimmer.</u>

7.2 Cutter Shaft Resharpening

If the cutter shaft does become dull after years of use, or after trimming several thousand cases, it can by resharpened at the factory. <u>Please return the Cutter Shaft Only. Do not send the entire Case Trimmer.</u>

7.3 Special Case Trimmer Pilots

Any special size Case Trimmer Pilot within our size range can be ordered through our Resellers or directly through Forster Products. Please specify the exact diameter desired.

8.0 FORSTER PRODUCTS CASE TRIMMER ACCESSORIES

Your Case Trimmer is a versatile tool that can be expanded with the accessories shown in Fig. 4 to perform a variety of case conditioning operations.



	Primer Pocket Cleaner Order No. PPC175: For .175" primer pockets							
Primer Pocket Cha		EV2: Primer Pocket Center (supports case mouth)	Order No. PPC210: For .210" primer pockets					
Order No. PPCE02: Primer Pocket C (supports case mo	enter PPCT01		Outside Neck Turner Pilots ler No. Bullet Dia. Order No. Bullet Dia. 2017 .172" OT2308 .308" 2204 .204" OT2311 .311" 2224 .224" OT2323 .323"					
		Jer No. OT: 1010: Use with separate, OT: caliber-specific OT: Outside Neck Turner Pilots OT: Neck Reamer	2243 .243" OT2333 .333" 2257 .257" OT2338 .388" 2264 .264" OT2358 .588" 2277 .277" OT2375 .375" 2284 .284" .284"					
Hollow Pointer Use Before Sizing Order No. Bullet Dia. NR1017 .172° NR1277 .277° NR1358 .358° NR1017 .172° NR1284 .224° NR1231 .311° NR1410 .410° NR1242 .224° NR1311 .311° NR1410 .410° NR1257 .257° NR1257 .257° NR1355 .355° NR1452 .452°								
Order No. Order No. NR1264 264" NR1355 .355" NR1458 .458" HP1016: 1/16", for rifle rounds HP1008: 1/8", for handgun rounds HP1008: 1/8", for handgun rounds Use After Sizing Use After Nite Dia. NR1220 .224" .2200" NR1220 .224" .2390"								
Our Power Adapter for Case Trimn Accessory Name	ners (PA1000) allows your case trimm Function	er to be powered by your	electric screwdriver or powe Used on the Original	r drill. Used on the				
Accessory Name	Function		Case Trimmer (CT1010) and the Power Case Trimmer (PT1010)	Classic Case Trimmer (CLCT100)				
Outside Neck Turner (OT1010)	Removes excess brass from the outs used after case sizing, this process p uniform thickness and exact outside after case sizing.	produces neck walls of	yes	no				
Neck Reamer (NR1###)	Removes excess brass from the inside well as the "dreaded donut" of materia fter repeated firings. Used before site of the sit	ial that can accumulate	yes	yes				
3-in-1 Case Mouth Cutter (3CUT-224, 3CUT-243, 3CUT-308)	Simultaneously chamfers the case no diameters, and trims case to length,		yes	no				
Primer Pocket Cleaner (PPC175: for small primer pockets, PPC21: for large primer pockets)	Easily and quickly removes primer an with the Primer Pocket Center .	nd powder residue. Used	yes	yes				
Primer Pocket Chamfering Tool (PPCT010)	Chamfers military primer pockets, rep the crimp from military cases. Used w Center.	-	yes	yes				
Hollow Pointer (HP1016, HP1018)	Hollow points most calibers of rifle ar 1/16" and 1/8" size drills. Long and s are available for hollow pointing long	hort case trimmer bases	yes	yes				

We recommend using our Resellers when ordering our products. Their experience and knowledge will help you select the best products that meet your specific requirements. In addition, they usually offer the best prices and convenient delivery options. To find a Reseller, go to **forsterproducts.com**, then click on **Locate a Reseller**. If your Reseller cannot supply you, please contact Forster Products directly.

WARRANTY

Forster Products warrants goods of its manufacture against defects in materials and workmanship for the life of the product. Parts which, by nature of their function, are subject to normal wear (such as springs, pins, etc.) and parts which have been altered, abused or neglected, are excluded from the warranty. If the product is deemed defective by workmanship or materials, it will be repaired, reconditioned or replaced (at Forster Products' option). This warranty supersedes all other warranties for Forster Products whether written or oral.

forsterproducts.com PT1010-001 Issue 4, July 2011