

User Instructions for the Short Handle for Co-Ax® Press

Issue 1

1.0 GENERAL INFORMATION

The Short Handle for Co-Ax Press is optional; it may be used when less leverage is needed such as for short rifle cartridges, most handgun calibers and seating and priming operations.

2.0 SAFETY INFORMATION

Always wear safety glasses.

3.0 PREPARATION

- Have a 1/8" Allen wrench available.

4.0 PROCEDURE

- Using the 1/8" Allen wrench, loosen the 1/4-28 Set Screw in the Co-Ax Press Yoke and remove the Standard Handle.
- Insert the Short Handle into the Yoke and tighten the Set Screw.

Figure 1. Short Handle



1.0 ORDERING INFORMATION

Table 1. Complete Product

Order Number	Description
SH1000	Short Handle for Co-Ax Press



6.0 RESELLERS

We recommend using our Resellers when ordering our products. Their experience and knowledge will help you select the best products that meet your specific requirements. In addition, they usually offer the best prices and convenient delivery options.

To find a Reseller, go to forsterproducts.com, then click on **Locate a Reseller**. If your Reseller cannot supply you, please contact Forster Products directly.

WARRANTY

All Forster Products are warranted against defects in materials and workmanship for the life of the product. Parts which, by nature of their function, are subject to normal wear (such as springs, pins, etc.) and parts which have been altered, abused or neglected, are excluded from the warranty. If the product is deemed defective by workmanship or materials, it will be repaired, reconditioned or replaced (at Forster's option). This warranty supersedes all other warranties for Forster Products whether written or oral.